

# BIG 3000

Power Sprayer w/ Two Counter-Rotating Double Ventilators.  
For Row Crops and Taller Trees Best Spraying.

Perfect-Powerful-Symmetric Spraying Left and Right.



## EXCLUSIVE ADVANTAGES:

- Two side intensive soft-way penetrating spraying.
- Soft-through foliage penetration.
- Balanced optimized air flows.
- Perfect symmetric spray Left and Right.
- Of Row Crops and Taller Trees.
- Spray swath up to 30 meters (95 feet) and more per side, horizontally.
- Spray swath up to 22 meters (70 feet) and more per side, vertically.
- Spray density adjust from 300 to 3000 litres/Hectar (32 to 320 US Gals/acre)
- Suggested tractor power 80 hp or more



# BIG 3000

## Power Sprayer w/ Two Counter-Rotating Double Ventilators.

### For Row Crops and Taller Trees Best Spraying. Perfect Powerful Symmetric Spraying Left and Right.



#### TECHNICAL FEATURES:

- Ventilator: Two Counter-Rotating Double Blowers, each one composed by a Fruit spray head and a Cannon spray head (Pict. 1).
- Each Spray head is angle adjustable independently (Pict. 2).
- Each double Ventilator remote adjustable from tractor seat.
- Spray nozzles diffused spray pattern, 2-spray selection, and Adjustable long spray pattern, 1-spray selection.
- Pressure pump delivery: 140 - 192 or 220 l/min (37-50-58 US Gals), pressure 0-50 bar (0-735 psi).
- Integrated fully automatic TIFONE Autofilter: the automatic continuous flushing self clean pressure filter (needing no manual discharge and no cleaning required) (Pict. 3).
- Telecontrol, the Super exact Pressure regulator; constant pressure.
- Precision Pressure gauge with 0,5 bar scale reading.
- Remote spray control by Tifone-Bosch valves (No. 4, one per each spray head).
- Instant Chemical Suction Probe "F2" for fast safe transfer of pest control dose of powder or granulate from the sac to the spray tank with instant mixing and instant discharge in the filling filter of spray tank (Pict. 4-5).
- Large foot-step.
- Robust ag-style chassis.
- Side antishock profile.
- Robust rear bumper.
- Robust front adjustable jockey wheel.

- Mud scrapers at wheels.
- Tyres: Nokia 400-60-15,5, low pressure.
- Dimensions:  
cm L 395, + tow bar  
88, W164, H198
- Empty weight kg 890.



Picture 1



Picture 2



Picture 4



Picture 3




Picture 5



#### SUGGESTED ACCESSORIES

1. Fast Tank Filling pump, self priming; hydromotor driven.
2. Two large s/steel containers for pesticides etc.
3. Hose reel w/10 meters pressure hose and pressure head lance for fast washing of tractor and machine after spraying.
4. Parabolic leaf spring suspension.
5. Braking system, road approved.
6. Extra width tires 500-60-15.



Tifone s.r.l. - via Modena, 248  
44044 Cassana - Ferrara - Italy - (uscita A/13 Ferrara Nord)  
Tel. +39 0532.730586 (r.a.) - Fax +39 0532.730588  
e-mail: tifone@tifone.com

[www.tifone.com](http://www.tifone.com)

