

### Sprayer with Very Robust, Compact Double Galvanised Frame.

New "entry level" line of tractor mounted sprayers: powerful, compact, robust, double galvanised frame, mechanical level immediately visible by the operator, original well-rounded shape, unique ventilation for effectiveness and penetration. Available with 300 and 400 L capacities.

Also available in version with "cannone" on 300 and 400 L.


#### Strengths:

- Frame with protective band on the ground for the tank against rough, muddy terrain.
- Round compact polyethylene tank with total facilitated emptying, no product residue.
- Mechanical level of the tank clearly visible by the operator.
- Pump with connecting rods in bronze 71 litres/minute 40 bars of pressure.
- Telecontrol Exact.
- Automatic Self-Clean Autofilter.
- Continuous automatic incremental agitation.
- Turbo 28" (70 cm) fan with 29,000 mc/h power.
- Axial Propeller adjustable instantly (9 possible inclination positions).
- Double Nozzles (6+6) with leak protection.



### MOUNTED VENTO with Axial Propeller / AP

	Tank L	Pump L/min	Nozzles N°	Propeller cm - max m³/h	Spray Width i - H / m	Dimensions L x W x H / cm	Weight kg	Code
328 AP	300	TEA71	6+6	70-29.000	3,5-4	100-114-120	165	APV03TV28PDV
428 AP	400	TEA71	6+6	70-29.000	3,5-4	105-114-120	212	APV04TV28PDV



### MOUNTED VENTO with Radial Propeller

	Tank L	Pump L/min	Nozzles N°	Propeller cm - max m³/h	Spray Width i - H / m	Dimensions L x W x H / cm	Weight kg	Code
300 CANNONE 45	300	TEA71	6+2	60-27.000	25-30	105-114-120	191	APV03TC40SDV
400 CANNONE 45	400	TEA71	6+2	70-29.000	25-30	118-114-120	227	APV04TC40SDV